

strapex

SMG 10

High performance strapping machine for 5/6 mm plastic strap

NEW

5 Highlights

Speed

- Up to 70 cycles per minute

Touch Panel

- Very easy handling

Simple technology

- Few moving parts
- Easily accessible (without tools)

Constant strap tension

- For small to large packages
- For soft and hard products

Pull-out dispenser

- Simple and rapid coil change



SMG 10

For small to large packages

User friendly

- Plug & Play: Very easy handling
- Mobile ready to use anywhere
- Adjustable working height
- All operating functions with foot pedal
- Strap tensions easily adjustable – for soft and hard products



Exceptionally easy operation

Strap tension adjustable with press button (+/-)

Strap tension "Soft" adjustable with press button

Robust, compact design

Easily accessible (without tools), simple and rapid coil change



Cost effective

- High availability
- For continuous operation
- Use of 5/6 mm PP strap – the alternative to wider strap
- Maintenance-friendly

Technical data

Machine

Performance per minute	Up to 70 cycles
Arch dimensions	
– Width x height	500 x 400 mm
	650 x 500 mm
Machine dimensions	
– Width x depth	900 x 565 mm
– Height	1320–1530 mm
Working height	820–930 mm
Electrical supply	1 x 230 V, 50 Hz
Strap tension	Up to 300 N
Seal	Heat seal
Weight	170 kg

Plastic strap

Strap coil, inner Ø 200 mm

Packages

Min. package size
– Width x height 100 x 5 mm

Options



Second foot pedal
for operation on both sides




Table photocell
for single, double or multiple strapping



Bundle stops
for precise positioning of loose packages

Strapex Advantage



Machine, strap and after-sales service as a total package

Strapex
Unit 50
Empire Industrial Park
Empire Close
GB-Aldridge, Walsall, WS9 8UQ

Phone +44 1922 742 500
Fax +44 1922 742 501

www.strapex.com